

Product Specifications

Printing Method	Drop-on demand 48 nozzle EPSON Stylus technology ink jet	
Print Speed	Letter Quality: 150 cps (10 cpi) 180 cps (12 cpi) 225 cps (15 cpi)	Draft: 250 cps (10 cpi) 300 cps (12 cpi) 375 cps (15 cpi)
Resident Bit-Mapped Fonts	EPSON Draft 10, 12, 15 EPSON Roman 10, 12, 15 proportional EPSON Sans Serif 10, 12, 15 proportional EPSON Courier 10, 12, 15 EPSON Prestige 10, 12, 15 EPSON Script 10, 12	
Scalable Fonts	EPSON Roman 8 to 32 points EPSON Sans Serif 8 to 32 points EPSON Roman T (PS) 8 to 32 points EPSON Sans Serif H (PS) 8 to 32 points	
Sound Level	45 dB(A)	
Printer Language	EPSON ESC/P 2™	
Maximum Graphics Resolution	360 x 360 dpi	
Print Enhancements	Bit-mapped fonts Double-wide, double-high, condensed Bit-mapped & scalable fonts Emphasized, underline, outline, shadow, italic, strike-through, double-underline, overscore, double-strike	
Dimensions	H x W x D 6" x 26" x 20" (with paper support) Weight 19 lbs.	
Input Buffer	128KB - Mixed text/graphics OFF 64KB - Mixed text/graphics ON	
Interfacing	Centronics®-compatible 8-bit parallel standard	
Character Sets	96 ASCII characters; 14 international character sets; 128 user-defined characters; 1 legal character set; 8 graphics character sets	
Electrical Requirements	120V AC+/- 10%; 50 to 60 Hz; 60 watts maximum	
Hardware Features	Control panel selection of fonts, form feed, default settings	
Print Direction	Bi-directional logic seeking in text and graphics modes	
Paper Feed Mechanism	Automatic, single sheet feed, continuous (with optional tractor unit)	
Printable Area (Minimum)	Margin top: .12" Margin left: .12" Margin bottom: .51" Margin right: .38" letter size; Margin right: .12" manual insertion	

EPSON Stylus™ 1000 Ink Jet Printer

Paper Handling

<i>Cut sheet (paper tray)</i>		
Size: Letter, Legal or Ledger	Thickness: .0026 to .0055"	
Width: 7.2" - 16.5"	Length: 7.2" - 11.7"	
Quality: Bond/plain paper	Weight: 14 to 24 lbs.	
<i>Cut sheet (manual insertion)</i>		
Width: 7.2" - 16.5"	Length: 7.2" - 16.5"	
Thickness: .0026 to .0043"	Weight: 14 to 24 lbs.	
Quality: Bond/plain paper		
<i>Continuous paper (with optional tractor unit)</i>		
Width: 4" - 16"	Thickness: .0026 to .0039"	
Quality: Plain paper	Weight: 14 to 22 lbs.	
<i>Envelopes</i>		
No. 6	No. 10	
Size (W x L)	6.5" x 3.6"	9.5" x 4.1"
Thickness	.0063 to .020"	.0063 to .020"
Quality: Bond/plain paper, air mail		
<i>Labels</i>		
Size (W x L): 2.5" x .94"	Width: 4" - 16" (base paper)	
Label thickness: <.0047"	Thickness: <.0078" (base paper)	
Quality: Plain paper		

Paper Width	5" to 16.5" (prints 11" x 17" in portrait orientation)
--------------------	---

Environmental Characteristics

Temperature	Operating: 50° to 95° (10° to 35°C) Storage: -4° to 122° (-20° to 50°C)
Humidity (no condensation)	Operating: 20 to 80% relative humidity Storage: 5 to 85% relative humidity

Safety Approvals

Safety Standards	UL1950 w/D3, CSA22.2 #220 with D3
R.F.I.	FCC Part 15 Subpart B class B

Reliability/Life Expectancy

Printer	MTBF 6,000 power on hours @ 25% duty cycle
Print head life	1 billion dots per nozzle
Ink cartridge (black)	700,000 characters

Product Codes

C114131	EPSON Stylus 1000
---------	-------------------

Optional Accessories

S020025	Ink Cartridge
C823051	Serial interface card
C823071	32KB Serial interface card
C823101	32KB Parallel interface card
C805311	Tractor unit
C823151	Twinox interface board
C823141	Coax interface board

Warranty	Two-year limited warranty in the U.S.
-----------------	---------------------------------------

Support	EPSON Connection information hotline 800-922-8911
	Faxback System 310-782-4214
	Electronic Bulletin Board 310-782-4531

EPSON®

USA: Call 1-800-289-3776 for the nearest dealer location
Epson America, Inc. 20770 Madrona Avenue, Torrance, CA 90503

Canada: Call 1-800-463-7766 Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1 Fax 416-498-4574

Latin America: Call 1-305-265-0092 Epson Latin American, Inc.
6303 Blue Lagoon Drive, Suite 390, Miami, Florida 33126 Fax 301-265-0097

Specifications are subject to change without notice. EPSON is a registered trademark and EPSON Stylus and ESC/P 2 are trademarks of Seiko Epson Corporation; EPSON Connection is a servicemark of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. EPSON disclaims any and all rights in these marks. © Copyright 1994 Epson America, Inc. CPD-1742 150M 4.94 AL